



F I L L I T

# D200 CONTACTLESS MPOS

- Contactless, Chip, Magstripe
- iOS & Android Compatible
- Visa & Mastercard NFC GPRS,
- Bluetooth, WiFi Apple MFi
- approved
- PCI PTS 3.x, SRED

The beautifully designed D200 integrates with any mobile payment app running on iOS or Android smart device via Bluetooth, WiFi, GPRS or cable connection. The D200 offers the latest PCI PTS 3.x security, SRED and Visa payWave & Mastercard PayPass contactless certification. Apple Inc. has given the D200 a special certification called MFi meaning that Apple has tested and approved the D200 to meet the highest performance standards for integration with any iPad or iPhone, including the new iPhone 6.

Payment Acceptance Made Easy



# D200 CONTACTLESS MPOS

## Features & Benefits



### High Reliability & Exceptional Performance

- Contactless NFC, EMV chip and magstripe enabled
- Featuring innovative touch-press key design
- Stylishly designed for comfort and convenience
- Large colour screen with user friendly interface
- Large memory capacity

### Flexible Platform

- Bluetooth, WiFi, GPRS and cable connectivity
- USB port for high speed data transmission
- Versatile Operating System



### Unprecedented Security

- PCI PTS 3.x approved, SRED
- Secure key embedded area

## Specifications

### Processor

32-bit ARM 11

### Memory

192MB (128MB Flash, 64MB SDRAM)

### Display

2.4 inch TFT colour LCD, 320 x 240 pixels

### Keypad

Touch- button input  
10 numeric & 5 function keys

### Magnetic Card Reader

Track1 / 2 / 3, Bi-directional

### Smart Card Reader

EMV L1 & L2 certified

### Contactless Card Reader

Mastercard Contactless & Visa payWave  
ISO14443 Type A/B  
Mifare®, Felica, NFC

### Card slots

2 SAMs  
or 1 SAM & 1 SIM (GPRS)

### Communication

Bluetooth 4.0 / WiFi / 3G

### Peripheral Ports

1 x Micro USB  
1 x RS232

### Security

PCI PTS 3.x certified  
SRED

### Environmental

0°C to 50°C (32°F to 122°F) operating temperature  
-20°C to 70°C (-4°F to 158°F) storage temperature  
10% to 93% relative humidity, non-condensing

### Voltage

Battery, 3.7V, 1300mAH  
Input: 100 - 240V AC, 50 / 60 Hz, 0.2A  
Output: 5VDC, 1A

### Physical

Length: 121mm  
Width: 72mm  
Height: 22.5mm

### Weight

165 g with battery

### Certifications

PCI PTS 3.x, SRED  
EMV Contact L1 & L2  
EMV Contactless L1  
Visa payWave  
Mastercard Contactless  
Mastercard TQM  
Visa Ready Mastercard  
MPOS

